

Disassembly

Disassemble the firearm to the point needed for inspection and cleaning. Remember you should not disassemble more than needed.

PRIOR TO CLEANING, ALWAYS BE SURE THE FIREARM IS UNLOADED.



Bore Cleaning

Select appropriate size patch holder, spear tip jag, cleaning patches, and bore brush.

1. Attach patch holder (slotted tip) or spear tip jag to cleaning rod.



2. Place appropriate size cleaning patch into patch holder slot, or pierce patch with spear point.



3. Saturate patch with 1 Step CLP and push through barrel. Run the cleaning rod in the same direction as the bullet travels (from breech to muzzle end).



4. Repeat Step #3, approximately 3-6 times, depending on fouling. **Tip: Let the 1 Step CLP do the work by soaking the bore 5-15 minutes. This is a great time to work on cleaning other parts of your firearm. Such as rails, the bolt, Bolt Carrier Group... etc.**

5. Remove patch holder/spear tip jag, and attach bore brush



6. Run Bore Brush through barrel 4-8 times. Depending on fouling. **Tip: Do not reverse brush in barrel during use.**

7. Remove Brush, and re-attach patch holder or spear tip jag.



8. Run cleaning patches through the bore until they come out clean.



9. Repeat process for heavily fouled barrels.

10. With Pro-Shot 1 Step CLP and Copper Solvent IV, you do not need to finish bore cleaning with an oil. Both already have an oil for rust and corrosion protection.

11. Check bore by using a Pro-Shot Original J, Chamber Flag Version, or XL Bore Illuminator.



Action Cleaning

Use a nylon or bronze bristle utility brush saturated with 1 Step CLP, Fouling Blaster, or Pro Clean Gun Cleaner #1 and scrub areas where powder residue and fouling build up (Slides, Forcing Cone, Top Strap, Ejectors, etc.) Use Pro-Shot Fouling Blaster/Pro Clean Gun cleaner for hard to reach areas of the action and trigger mechanism. (Ensure to properly lubricate after using Fouling Blaster or Pro Clean Gun Cleaner #1).



Original J Bore Light

THE FAMOUS AND ORIGINAL NO BATTERY GUN BORE LIGHT

- Fast & Easy way to check barrels for wear or obstructions.
- Illuminates bore with Ambient or UV Light
- Fits in most Handguns/Rifle Chamber
- Illuminates bore with no glare
- Short End of the J goes to the chamber
- Poly Carbonate



Original J Version

XL Version for Shotgun

Chamber Flag Bore Light

Lubrication

Lightly lubricate all surfaces that have been degreased and all moving parts. This will ensure proper functioning, aid in rust prevention, and increase the firearm's life. (Do Not Over Lubricate, this can cause the action to become gummy, allowing dust and debris to collect).

Sparingly use Pro-Shot Zero-Friction High Tech Lubricant, 1 Step CLP, or Pro Gold Grease to protect all moving parts and inhibit rust.

Temperature Operating Range:

Great for Extreme Weather Conditions:

- Zero-Friction -75° to 450°F
- 1 Step CLP -50° to 575°F

Excellent for Warm Conditions

- Pro Gold Grease Range 32° to 450°F



Reassemble

After reassembly, wipe down outside of metal on firearm with metal care cloth, silicone cloth, or cotton cloth with light oil.

Sold Separately Item# Metal Care Cloth (#MMC), Silicone Cloth (#SILC), and Cotton Cloths (#WIPE, TWC).



Pro-Shot Cleaning Rods

- American processed steel made to Pro-Shot specs.
- Our Stainless Steel is less hard than barrel steel.
- Heat treated to add to the durability and strength.
- Centerless ground to smooth the metal.
- Exclusive to Pro-Shot Burnishing builds the coating into the surface of the rod giving it a mirror-like finish.
- Stainless rods are resistant to all solvents.
- Coated rods have the same process plus exclusive Pro-Tuff Coating.



**HAND CRAFTED
AMERICAN MADE**

Pro-Shot Patches **WORLD FAMOUS SINCE 1982**

- American grown cotton and made to Pro-Shot spec.
- Superior thread count woven in material for trapping fouling.
- Double Napped for maximum absorbency, will not shrivel up like polyester patches no matter what solvent used.
- Packaged in Zip Top convenient bags.



Patch Size Guide:

¾" Square Fits .17-.22 Cal. Rimfire
 1" Round Fits .22-.270 Cal.
 1 1/8" Square Fits .22-.270 Cal.
 1 3/8" Square Fits 6-7mm
 1 ½" Square Fits 7mm-.38 Cal. / 6mm Benchrest
 2" Round Fits .270-.38 Cal.
 2 ¼" Square Fits .38-.45 Cal. / 410-20 GA
 2 ½" Round Fits .45-.58 Cal. Black Powder
 3" Square Fits 12-16 GA Shotgun

Pro-Shot Bore Brushes

- Superior Quality Benchrest Bore Brushes are made with: Brass Core and Bronze Bristles - Brass core holds the bristles better than an aluminum core and Pro-Shot brushes have more bristles per inch.
- Looped End - A no-harm brush that protects the barrel during use.
- Brass Coupling - Holds the core together better than aluminum, making it a stouter brush.
- Pro-Shot brushes are sized 14 thousandths over the caliber/mm bore diameter. Competition is only 7 thousandths, making the Pro-Shot brush clean better and last longer.
- **Pro-Shot Benchrest Quality Brushes make the cleaning process faster & easier!**



Optics Cleaning

Item# LCK-BASIC (Pictured Below), and #LCK (Optics Cleaning in Tactical Pouch)

- Remove as much dust and dirt as possible from the lens with soft bristle lens brush.
 - Apply Lens Cleaning solution to the lens.
 - Use a circular motion to gently remove oil, fingerprints, and grime from the lens surface, working from the center outward. When wiping, apply only enough pressure to remove smudge.
 - Use cotton swabs for hard to reach areas.
 - Extremely dirty lenses should be washed with soap and water then dried with microfiber lens cloth.
- Next, apply Anti-Fog lens cleaner as a protectant and dry with lens tissue.
- To remove dust only: brush lens gently with lens brush.



**MADE
IN THE
USA**



"FIREARMS CLEANING ACCESSORIES IS OUR PASSION, SERVICE IS OUR SPECIALTY!"

CLEANING INSTRUCTIONS

www.ProShotProducts.com

Email: service@proshotproducts.com

Phone: 217-824-9133

Gun Safety Rules of Firearms



Things to know before cleaning:

- Always check to make sure your gun is unloaded before cleaning.
- Do not have any ammunition around cleaning process.
- Inspect your gun as you clean. Check your firearms for wear and cracks when you clean. Consult a qualified gunsmith for any necessary repairs.
- Don't disassemble your gun more than necessary. Only disassemble gun to the point needed to reach areas where powder residue and fouling accumulate (bore, chamber, bolt, etc.). Refer to owners manuals for instructions.

Recommendations

- Use a cleaning mat to save time and cleanup.
- When using Pro-Shot 1 Step CLP or Copper Solvent IV, let the cleaner set for 5-15 minutes in the bore so the penetrating agents and additives break the fouling loose.
- Pro-Shot Spear Tip Jag: Using a spear tip jag is a superior way to remove fouling from your barrel. It gives the patch constant pressure in the bore and traps fouling in the rings.
- Use the appropriate size Bore Brush, Jag, or Mop. Pro-Shot accessories are sized caliber specific and will make the cleaning process faster and easier.
- Use a bore guide on all bolt action rifles. Use a muzzle guard on lever action rifles and revolvers. These accessories keep the rod centered during cleaning and stops fouling from entering the action on bolt action rifles.